

## Family

# Fini


A single luminaire, Fini, is an invisible luminaire that will enhance the atmosphere of any interior. The luminaires are adjustable which will help you achieve an ideal light effect without any shadows. You can line up a number of single luminaires that come in the lengths of 850 mm, 1130 mm, 1410 mm or 1690 mm. We offer three levels of luminous flux, a tuneable white version and an important IP40 protection. The height available for installing the luminaire should be at least 25 cm, which will help achieve an optimal light effect by adjusting the tilt of the luminaire.

Type of installation	Surface
Light distribution	Direct
Colour of the luminaires	Silver
Colour Temperature	3000 K warm white, 4000 K cool white
Material	Aluminium
Light source	LED MODUL
MacAdam Light source	3
Connection of the luminaires	ON/OFF DALI
Lifetime	L80/B20 50 000 hours
Warranty	60 months

## Luminaire family variants Fini



## Fini



### Assembly



### Light distribution



### Energy class

energy\_class\_g

### Marks

Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
160-202K-15GEE/840, E	850 × 68 × 60	11.2	1450	4000	< 23
160-202K-15GGE/840, E	850 × 68 × 60	15.8	2000	4000	< 24.1
160-202K-15GHE/840, E	850 × 68 × 60	31.4	3650	4000	< 26.2
160-202K-20GEE/840, E	1130 × 68 × 60	14.8	1950	4000	< 23.1
160-202K-20GGE/840, E	1130 × 68 × 60	20.8	2650	4000	< 24.1
160-202K-20GHE/840, E	1130 × 68 × 60	41.8	4900	4000	< 26.3
160-202K-25GEE/840, E	1410 × 68 × 60	18.8	2500	4000	< 23.2
160-202K-25GGE/840, E	1410 × 68 × 60	27.7	3340	4000	< 24.1
160-202K-25GHE/840, E	1410 × 68 × 60	52.3	6100	4000	< 26.3
160-202K-30GEE/840, E	1690 × 68 × 60	22.4	2950	4000	< 23.1
160-202K-30GGE/840, E	1690 × 68 × 60	31.3	4000	4000	< 24.2
160-202K-30GHE/840, E	1690 × 68 × 60	63.2	7300	4000	< 26.3

These codes represent luminaires without a profile with chromaticity temperature 4000K and opal diffuser.

## Notes

Colour of the  
luminaires



Colour Temperature

3000 K warm white  
4000 K cool white

Optic system

Opal diffuser

Connection of the  
luminaires

ON/OFF  
DALI

Ra

80

Luminaires come complete with all necessary accessories.

## Legend

### Type of installation

	Recessed lights		Wall mounted lights
	Semi-recessed luminaire		Suspended lights
	Surface lights		Free-standing lights
	3 circuit track lights		Table lamp lights

### Light distribution

	Direct luminaire
	Direct-indirect luminaire
	Indirect luminaire

### Light source

	<b>Tunable White</b> adjusting the color temperature		<b>RealWhite</b> true display of white color
	<b>RealColour</b> true display of colors Ra≥97		<b>StrongColour</b> highlight one color

### Marks

	Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
	European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
	Luminaires are certified according to the European ENEC system
	Recommended mounting hole size

**IPxy** IP code indicating the degree of protection of live parts

**EAC** Eurasian Conformity

## 11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

**Optic system**

**Electrical connection**

**Colour**

### Optic system

<b>B</b>	Microprismatic system, low UGR	<b>L</b>	Plain aluminium reflector
<b>C</b>	Clear cover	<b>M</b>	Matt parabolic louvre
<b>D</b>	Asymmetric reflector	<b>S</b>	SPOT - narrow angle
<b>E</b>	Polished parabolic louvre, high LOR	<b>U</b>	MEDIUM - middle angle
<b>F</b>	FLOOD - wide angle	<b>W</b>	Wide beam angle
<b>I</b>	Microprismatic optical system	<b>Z</b>	Plastic louver, low UGR
<b>K</b>	Opal diffuser		

### Electrical connection

<b>/BT</b>	Luminaires controlled via Bluetooth technology	<b>P</b>	Sensor and electronic ballast
<b>D</b>	DALI dimmable	<b>T</b>	By switch dimmable (touch dimm)
<b>E</b>	Electronic ballast non-dimmable	<b>TD</b>	DALI or by switch (touch dimm) dimmable
<b>M</b>	Electronic ballast non-dimmable with 1h emergency	<b>U</b>	Dimmable luminaire with dimmer on the luminaire
<b>M3</b>	Electronic ballast non-dimmable with 3h emergency		

### Colour

<b>W</b>		<b>B</b>		<b>S</b>	
<b>1021</b>		<b>2000</b>		<b>3020</b>	
<b>5015</b>		<b>6018</b>		<b>7016</b>	
<b>9006</b>		<b>9010</b>			

### Značky typu

	Smart – Luminaire or the lighting system controlled by motion, daylight or via smart devices using Bluetooth technology
	Acoustic – Luminaire with acoustic absorption properties which reduce disturbing noise and improve the acoustics of the room
	Multiwatt – Luminaires with individually adjustable luminous flux using a special antenna or mobile application

**UGR** UGR – The luminaire suitable for office spaces