



## Luminaire

# Lina60-S

04S-200W-30GGD/930, B



EPD®

You will appreciate the L-Click system on the Lina60-S luminaire with a direct light distribution, which effectively saves you both time and money. How? The module simply clicks into the profile, so a lot of work is saved during assembly. This solution also prevents the direct touch of the LED technology and lengthens its operating life. The Lina60-S lighting system can be assembled creating endless lines and a big variety of shapes. In addition to great power output, the luminaire also has a great price. It will find its use in commercial, social and public spaces.

## Technical drawing



|                           |   |
|---------------------------|---|
| Type of installation      | Recessed, Surface, Wall mounted, Suspended        |
| Light distribution        | Direct  |
| Luminaire shape           | Linear  |
| Colour of the luminaires  | Black   |
| Material                  | Aluminium   |
| Lifetime                  | L80/B20 50 000 hours                              |
| Warranty                  | 5 years   |
| Description of luminaires | Luminaire recessed/surface/wall mounted/suspended |
| Dimensions                | 561 mm × 57 mm × 67 mm                            |
| Light source              | LED MODUL   |

|  |                   |
|--|-------------------|
| Type of optical system                 | Reflector         |
| Luminous flux*                         | 1650 lm           |
| Colour Temperature                     | 3000 K warm white |
| Luminous efficacy                      | 83 lm/W           |
| MacAdam Light source                   | 3                 |
| Colour rendering index                 | 90                |
| Beam angle                             | 68°               |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 24.3              |

## Curve



Luminaire power input\* 60 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00354, K**  
cable 5x0,75 1000mm



**00-00355, K**  
cable 5x0,75 2000mm



**00-00356, K**  
cable 5x0,75 4000mm



**00-00357, K**  
cable 5x0,75 6000mm



**00-00363, K**  
cable 5x1,5 2000mm



**00-00364, K**  
cable 5x1,5 4000mm



**00-00365, K**  
cable 5x1,5 6000mm



**00-00366, K**  
cable 7x0,75 2000mm



**00-00367, K**  
cable 7x0,75 4000mm



**00-00368, K**  
cable 7x0,75 6000mm



**00-00370, B**  
ceiling cup 80x80x32mm



**00-00501**  
wire for emergency  
lighting XX-XXXX-40



**00-00600, F**  
ceiling fastening for  
luminaires 132-5xxK,  
04-2000x, 05-2000x,  
09-200x - 1 piece



**00-20700, B**  
2 pcs of wall fastening  
Lipo/Lina



**04-00200, N**  
straight connector



**04-01200, F**  
Accessory for gear-tray  
release



**04-20101, B**  
2xend cap - metal, 5-  
conductor terminal box,  
grommet



**04-20103, B**  
2xend cap - plastic, 5-  
conductor terminal box,  
grommet



**04-20900, F**  
bracket for installation  
of suspended type of  
profile as recessed  
trimless