


**Luminaire**

# Lina80-S

05S-000K-15GGE/840, W


**EPD<sup>®</sup>**

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

**Technical drawing**


|                                   |                        |
|-----------------------------------|------------------------|
| Type of installation              | Recessed               |
| Light distribution                | Direct                 |
| Luminaire shape                   | Linear                 |
| Colour of the luminaires          | White                  |
| Material                          | Aluminium              |
| Lifetime                          | L90/B50 60 000 hours   |
| Warranty                          | 60 months              |
| Description of luminaires         | Luminaire recessed     |
| Dimensions                        | 842 mm × 98 mm × 84 mm |
| Light source                      | LED MODUL              |
| Type of optical system            | Opal diffuser          |
| Luminous flux                     | 2450 lm ± 10 %         |
| Colour Temperature                | 4000 K cool white      |
| Luminous efficacy                 | 132 lm/W               |
| MacAdam Light source              | 2                      |
| Colour rendering index            | 80                     |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 25                     |

Luminaire power input 18.6 W  $\pm$  10 %

---

Connection of the luminaires Electronic ballast non-dimmable

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

 **CE** IP 40

## Downloads

Installation instructions



Photos



## Accessories



**00-00100, W**  
2xend cap - metal, 3-  
conductor terminal box,  
grommet; Lipo80



**00-00200, N**  
straight connector



**00-00500**  
wire for emergency  
lighting XX-XXXX-20



**00-01200, F**  
Accessory for gear-tray  
release