



## Luminaire

# Lina80-S

05S-200I-35GHTD/830, W



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



|                                   |   |
|-----------------------------------|---|
| Type of installation              | Recessed, Surface, Wall mounted, Suspended, 3 circuit track       |
| Light distribution                | Direct  |
| Luminaire shape                   | Linear  |
| Colour of the luminaires          | White   |
| Material                          | Aluminium   |
| Lifetime                          | L80/B10 70 000 hours  |
| Warranty                          | 60 months   |
| Description of luminaires         | Luminaire recessed/surface/wall mounted/suspended/3 circuit track |
| Dimensions                        | 1964 mm × 80 mm × 93 mm   |
| Light source                      | LED MODUL   |
| Type of optical system            | Microprisma   |
| Luminous flux                     | 7490 lm ± 10 %  |
| Colour Temperature                | 3000 K warm white   |
| Luminous efficacy                 | 98 lm/W   |
| MacAdam Light source              | 2   |
| Colour rendering index            | 80  |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 22.1  |

|                              |   |
|------------------------------|---|
| Luminaire power input        | 76.7 W $\pm$ 10 %                       |
| Connection of the luminaires | DALI or by switch (touch dimm) dimmable |
| Electrical voltage           | 220-240V                                |
| Frequency                    | 50/60Hz                                 |

  IP 40

## Downloads

Installation instructions



Photos



**Accessories**

**00-00200, N**  
 straight connector

**00-00300, N**  
 wire suspension  
 2000mm

**00-00301, N**  
 wire suspension  
 4000mm

**00-00302, N**  
 wire suspension  
 6000mm

**00-00354, K**  
 cable 5x0,75 1000mm

**00-00355, K**  
 cable 5x0,75 2000mm

**00-00356, K**  
 cable 5x0,75 4000mm

**00-00357, K**  
 cable 5x0,75 6000mm

**00-00363, K**  
 cable 5x1,5 2000mm

**00-00364, K**  
 cable 5x1,5 4000mm

**00-00365, K**  
 cable 5x1,5 6000mm

**00-00366, K**  
 cable 7x0,75 2000mm

**00-00367, K**  
 cable 7x0,75 4000mm

**00-00368, K**  
 cable 7x0,75 6000mm

**00-00370, W**  
 ceiling cup 80x80x32mm

**00-00600, F**  
 ceiling fastening for  
 luminaires 132-5xxK,  
 04-2000x, 05-2000x,  
 09-200x - 1 piece

**00-01200, F**  
 Accessory for gear-tray  
 release

**00-20101, W**  
 2xend cap - metal, 5-  
 conductor terminal box,  
 grommet; Lipo80/Lina80

**00-20103, W**  
 2xend cap - plastic, 5-  
 conductor terminal box,  
 grommet; Lipo80/Lina80

**00-20700, W**  
 2 pcs of wall fastening  
 Lipo/Lina

**00-20900, F**  
 bracket for installation  
 of suspended type of  
 profile as recessed  
 trimless

**00-21300, W**  
 Lipo80-S, Lina80-S -  
 pendant profile for track  
 luminaires; l = 1122mm

**00-21301, W**  
 Lipo80-S, Lina80-S -  
 pendant profile for track  
 luminaires; l = 2242mm

**00-51300, W**  
 set for suspension into  
 3-phase track, non-  
 dimmable luminaires

**00-51301, W**  
 set for suspension into  
 3-phase track, dimmable  
 luminaires