



Luminaire

Lina80-S

05S-200I-40GGM/830, S



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

Technical drawing



Type of installation	Recessed, Surface, Wall mounted, Suspended, 3 circuit track
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L90/B50 60 000 hours
Warranty	60 months
Description of luminaires	Luminaire recessed/surface/wall mounted/suspended/3 circuit track
Dimensions	2244 mm × 80 mm × 93 mm
Light source	LED MODUL
Type of optical system	Microprisma
Luminous flux	5190 lm ± 10 %
Colour Temperature	3000 K warm white
Luminous efficacy	105 lm/W
MacAdam Light source	2
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	20.3

Luminaire power input	49.6 W \pm 10 %
Connection of the luminaires	Electronic ballast non-dimmable with 1h emergency
Electrical voltage	220-240V
Frequency	50/60Hz

 **CE** IP 40

Downloads

Installation instructions



Photos



Accessories


00-00200, N
straight connector



00-00300, N
wire suspension
2000mm



00-00301, N
wire suspension
4000mm



00-00302, N
wire suspension
6000mm



00-00363, K
cable 5x1,5 2000mm



00-00364, K
cable 5x1,5 4000mm



00-00365, K
cable 5x1,5 6000mm



00-00370, S
ceiling cup 80x80x32mm



00-00600, F
ceiling fastening for
luminaires 132-5xxK,
04-2000x, 05-2000x,
09-200x - 1 piece



00-01200, F
Accessory for gear-tray
release



00-20101, S
2xend cap - metal, 5-
conductor terminal box,
grommet; Lipo80/Lina80



00-20103, S
2xend cap - plastic, 5-
conductor terminal box,
grommet; Lipo80/Lina80



00-20700, S
2 pcs of wall fastening
Lipo/Lina



00-20900, F
bracket for installation
of suspended type of
profile as recessed
trimless



00-21300, S
Lipo80-S, Lina80-S -
pendant profile for track
luminaires; l = 1122mm



00-21301, S
Lipo80-S, Lina80-S -
pendant profile for track
luminaires; l = 2242mm



00-51300, S
set for suspension into
3-phase track, non-
dimmable luminaires



00-51301, S
set for suspension into
3-phase track, dimmable
luminaires