



Luminaire

Lina80-S

05S-200K-35GGE/830, B



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

Technical drawing



Type of installation	Recessed, Surface, Wall mounted, Suspended, 3 circuit track
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L90/B50 60 000 hours
Warranty	5 years
Description of luminaires	Luminaire recessed/surface/wall mounted/suspended/3 circuit track
Dimensions	1964 mm × 80 mm × 93 mm
Weight	7.1 kg
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux*	5450 lm
Colour Temperature	3000 K warm white
Luminous efficacy	126 lm/W
MacAdam Light source	2
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	24.9

Luminaire power input*	43.4 W
Connection of the luminaires	ON/OFF
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 40

*±10 %

Downloads

Installation instructions



Photos



Accessories

00-00200, N
 straight connector

00-00300, N
 wire suspension
 2000mm

00-00301, N
 wire suspension
 4000mm

00-00302, N
 wire suspension
 6000mm

00-00350, K
 cable 3x0,75 1000mm

00-00352, K
 cable 3x0,75 2000mm

00-00358, K
 cable 3x0,75 4000mm

00-00360, K
 cable 3x0,75 6000mm

00-00363, K
 cable 5x1,5 2000mm

00-00364, K
 cable 5x1,5 4000mm

00-00365, K
 cable 5x1,5 6000mm

00-00370, B
 ceiling cup 80x80x32mm

00-00501
 wire for emergency
 lighting XX-XXXX-40

00-00600, F
 ceiling fastening for
 luminaires 132-5xxK,
 04-2000x, 05-2000x,
 09-200x - 1 piece

00-01200, F
 Accessory for gear-tray
 release

00-20100, B
 2xend cap - metal, 3-
 conductor terminal box,
 grommet; Lipo80/Lina80

00-20102, B
 2xend cap - plastic, 3-
 conductor terminal box,
 grommet; Lipo80/Lina80

00-20700, B
 2 pcs of wall fastening
 Lipo/Lina

00-20900, F
 bracket for installation
 of suspended type of
 profile as recessed
 trimless

00-21300, B
 Lipo80-S, Lina80-S -
 pendant profile for track
 luminaires; l = 1122mm

00-21301, B
 Lipo80-S, Lina80-S -
 pendant profile for track
 luminaires; l = 2242mm

00-51300, B
 set for suspension into
 3-phase track, non-
 dimmable luminaires

00-51301, B
 set for suspension into
 3-phase track, dimmable
 luminaires