



Luminaire

Lina80-S

05S-220I-20GGTD/830, S



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

Technical drawing



| | |
|----------------------|---|
| Type of installation | Recessed, Surface, Wall mounted, Suspended, 3 circuit track |
|----------------------|---|

| | |
|--------------------|--------|
| Light distribution | Direct |
|--------------------|--------|

| | |
|-----------------|--------|
| Luminaire shape | Corner |
|-----------------|--------|

| | |
|--------------------------|--------|
| Colour of the luminaires | Silver |
|--------------------------|--------|

| | |
|----------|-----------|
| Material | Aluminium |
|----------|-----------|

| | |
|----------|----------------------|
| Lifetime | L90/B50 50 000 hours |
|----------|----------------------|

| | |
|----------|-----------|
| Warranty | 60 months |
|----------|-----------|

| | |
|---------------------------|---|
| Description of luminaires | Luminaire recessed/surface/wall mounted/suspended/3 circuit track |
|---------------------------|---|

| | |
|------------|-------------------------|
| Dimensions | 613 mm × 613 mm × 93 mm |
|------------|-------------------------|

| | |
|--------------|-----------|
| Light source | LED MODUL |
|--------------|-----------|

| | |
|------------------------|-------------|
| Type of optical system | Microprisma |
|------------------------|-------------|

| | |
|---------------|----------------|
| Luminous flux | 2590 lm ± 10 % |
|---------------|----------------|

| | |
|--------------------|-------------------|
| Colour Temperature | 3000 K warm white |
|--------------------|-------------------|

| | |
|-------------------|----------|
| Luminous efficacy | 104 lm/W |
|-------------------|----------|

| | |
|----------------------|---|
| MacAdam Light source | 2 |
|----------------------|---|

| | |
|------------------------|----|
| Colour rendering index | 80 |
|------------------------|----|

| | |
|-----------------------------------|------|
| UGR max. X=4H Y=8H, ρ=70,50,20 | 20.3 |
|-----------------------------------|------|

| | |
|------------------------------|---|
| Luminaire power input | 24.8 W \pm 10 % |
| Connection of the luminaires | DALI or by switch (touch dimm) dimmable |
| Electrical voltage | 220-240V |
| Frequency | 50/60Hz |

 **CE** IP 40

Downloads

Installation instructions



Photos

