



## Luminaire

# Ilbi


108-301K-20GEE/830, W



When Matúš Opálka closed himself into his study for a month, we were wondering what he would come up with. He designed lighting that gives off a gentle but luxurious effect. The indirect two-sided emission with reflection from the wall creates a pleasantly soft light with adjustable intensity. The aluminum profile has been fitted with powerful LED boards. We offer a separate wall-mounted luminaire in black, silver and white embodiment. If you are looking to light up meeting rooms, all kinds of corridors, halls, conference and banquet halls, the Ilbi is for you.


Design Matúš Opálka

## Technical drawing



|                           |  |
|---------------------------|--|
| Type of installation      | Surface, Wall mounted, Suspended         |
| Light distribution        | Indirect                                 |
| Luminaire shape           | Linear                                   |
| Colour of the luminaires  | White                                    |
| Material                  | Aluminium                                |
| Lifetime                  | L80/B20 50 000 hours                     |
| Warranty                  | 60 months                                |
| Description of luminaires | Luminaire surface/wall mounted/suspended |
| item description          | independent luminaire                    |
| Dimensions                | 616 mm × 37 mm × 106 mm                  |
| Weight                    | 2 kg                                     |
| Light source              | LED MODUL                                |
| Type of optical system    | Opal diffuser                            |
| Luminous flux             | 2260 lm ± 10 %                           |
| Colour Temperature        | 3000 K warm white                        |
| Luminous efficacy         | 117 lm/W                                 |
| MacAdam Light source      | 3  |
| Colour rendering index    | 80                                       |

## Curve



Luminaire power input 19.3 W  $\pm$  10 %

Connection of the luminaires Electronic ballast non-dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

## Downloads

Installation instructions



Photos



**Accessories****00-00350, K**  
cable 3x0,75 1000mm**00-00352, K**  
cable 3x0,75 2000mm**00-00354, K**  
cable 5x0,75 1000mm**00-00355, K**  
cable 5x0,75 2000mm**00-00370, W**  
ceiling cup 80x80x32mm**01-0007, N**  
wire suspension  
2000mm**108-0002, F**  
wall fastening for  
108-301K