



## Luminaire

# Ilbi


108-301K-50GEE/830, S



When Matúš Opálka closed himself into his study for a month, we were wondering what he would come up with. He designed lighting that gives off a gentle but luxurious effect. The indirect two-sided emission with reflection from the wall creates a pleasantly soft light with adjustable intensity. The aluminum profile has been fitted with powerful LED boards. We offer a separate wall-mounted luminaire in black, silver and white embodiment. If you are looking to light up meeting rooms, all kinds of corridors, halls, conference and banquet halls, the Ilbi is for you.

Design Matúš Opálka

## Technical drawing



Type of installation	Surface, Wall mounted, Suspended
Light distribution	Indirect
Luminaire shape	Linear
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/wall mounted/suspended
item description	independent luminaire
Dimensions	1456 mm × 37 mm × 106 mm
Weight	4.5 kg
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux*	5660 lm
Colour Temperature	3000 K warm white
Luminous efficacy	117 lm/W
MacAdam Light source	3
Colour rendering index	80

## Curve



Luminaire power 48.3 W  
input\*

Connection of the ON/OFF  
luminaires

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00350, K**  
cable 3x0,75 1000mm



**00-00352, K**  
cable 3x0,75 2000mm



**00-00354, K**  
cable 5x0,75 1000mm




**00-00355, K**  
cable 5x0,75 2000mm



**00-00370, S**  
ceiling cup 80x80x32mm



**01-0007, N**  
wire suspension  
2000mm



**108-0002, F**  
wall fastening for  
108-301K