


Luminaire

Kvado

119-214I-40GED/840, W



The Kvado family luminaires are made of a high-quality aluminium profile and are available in versions with both direct and direct-indirect distribution of light. Their simple shape and quality of workmanship make them suitable for any space. The luminaires can combine an opal diffuser or microprismatic optics. Thanks to all this, you can use them in administrative buildings, shopping centres, public spaces or residential buildings. Both pendant and surface versions are available in various colours according to our Halla RAL chart.

Technical drawing


Type of installation	Surface, Wall mounted, Suspended
Light distribution	Direct
Luminaire shape	Angular
Colour of the luminaires	White
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/wall mounted/suspended
Dimensions	600 mm × 600 mm × 70 mm
Weight	7.8 kg
Light source	LED MODUL
Type of optical system	Microprisma
Luminous flux*	3830 lm
Colour Temperature	4000 K cool white
Luminous efficacy	112 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, $\rho=70,50,20$	16.7

Luminaire power input* 34.1 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

  IP 20

*±10 %

Downloads

Installation instructions



Photos



Accessories



00-00333, W
suspension set
2000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



00-00340, W
suspension set
4000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



00-00344, W
suspension set
6000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



19-0009, W
Mounting distance kit for square
luminaire, circular 370 mm