



## Luminaire


# Kvado

119-214K-90GED/840, W



The Kvado family luminaires are made of a high-quality aluminium profile and are available in versions with both direct and direct-indirect distribution of light. Their simple shape and quality of workmanship make them suitable for any space. The luminaires can combine an opal diffuser or microprismatic optics. Thanks to all this, you can use them in administrative buildings, shopping centres, public spaces or residential buildings. Both pendant and surface versions are available in various colours according to our Halla RAL chart.

## Technical drawing



Type of installation	Surface, Suspended
Light distribution	Direct
Luminaire shape	Angular
Colour of the luminaires	White
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/suspended
Dimensions	900 mm × 900 mm × 70 mm
Weight	17.4 kg
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux*	10530 lm
Colour Temperature	4000 K cool white
Luminous efficacy	137 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, $\rho=70,50,20$	21.5

Luminaire power  
input\* 76.7 W

---

Connection of the  
luminaires DALI

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00333, W**  
suspension set  
2000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00340, W**  
suspension set  
4000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00344, W**  
suspension set  
6000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**19-0009, W**  
Mounting distance kit for square  
luminaire, circular 370 mm