


Luminaire

Lina80-S

11S-501B-40GHE/830, W


EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

Technical drawing


| | |
|----------------------|-------------------------|
| Type of installation | Wall mounted, Suspended |
|----------------------|-------------------------|

| | |
|--------------------|-----------------|
| Light distribution | Direct-indirect |
|--------------------|-----------------|

| | |
|-----------------|--------|
| Luminaire shape | Linear |
|-----------------|--------|

| | |
|--------------------------|-------|
| Colour of the luminaires | White |
|--------------------------|-------|

| | |
|----------|-----------|
| Material | Aluminium |
|----------|-----------|

| | |
|----------|----------------------|
| Lifetime | L90/B50 50 000 hours |
|----------|----------------------|

| | |
|----------|---------|
| Warranty | 5 years |
|----------|---------|

| | |
|---------------------------|----------------------------------|
| Description of luminaires | Luminaire wall mounted/suspended |
|---------------------------|----------------------------------|

| | |
|------------|-------------------------|
| Dimensions | 2244 mm × 80 mm × 93 mm |
|------------|-------------------------|

| | |
|--------------|-----------|
| Light source | LED MODUL |
|--------------|-----------|

| | |
|------------------------|------------|
| Type of optical system | MP LOW UGR |
|------------------------|------------|

| | |
|----------------|----------|
| Luminous flux* | 11530 lm |
|----------------|----------|

| | |
|--------------------|-------------------|
| Colour Temperature | 3000 K warm white |
|--------------------|-------------------|

| | |
|-------------------|----------|
| Luminous efficacy | 119 lm/W |
|-------------------|----------|

| | |
|----------------------|---|
| MacAdam Light source | 2 |
|----------------------|---|

| | |
|------------------------|----|
| Colour rendering index | 80 |
|------------------------|----|

| | |
|-----------------------------------|------|
| UGR max. X=4H Y=8H, ρ=70,50,20 | 15.2 |
|-----------------------------------|------|

Curve



Luminaire power input* 97.2 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

* $\pm 10\%$

Downloads

Installation instructions



Photos

