



## Luminaire

# Lina80-S

11S-501I-25GHE/830, W



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



Type of installation Wall mounted, Suspended

Light distribution Direct-indirect

Luminaire shape Linear

Colour of the luminaires White

Material Aluminium

Lifetime L90/B50 50 000 hours

Warranty 5 years

Description of luminaires Luminaire wall mounted/suspended

Dimensions 1403 mm × 80 mm × 93 mm

Weight 5.5 kg

Light source LED MODUL

Type of optical system Microprisma

Luminous flux 7020 lm ± 10 %

Colour Temperature 3000 K warm white

Luminous efficacy 102 lm/W

MacAdam Light source 2

Colour rendering index 80

UGR max. X=4H 18.3  
Y=8H,  $\rho=70,50,20$

## Curve



Luminaire power input 68.8 W ± 10 %

Connection of the luminaires Electronic ballast non-dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

## Downloads

Installation instructions



Photos



**Accessories**


**00-00200, N**  
straight connector



**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00352, K**  
cable 3x0,75 2000mm



**00-00355, K**  
cable 5x0,75 2000mm



**00-00356, K**  
cable 5x0,75 4000mm



**00-00358, K**  
cable 3x0,75 4000mm



**00-00360, K**  
cable 3x0,75 6000mm



**00-00363, K**  
cable 5x1,5 2000mm



**00-00364, K**  
cable 5x1,5 4000mm



**00-00365, K**  
cable 5x1,5 6000mm



**00-00370, W**  
ceiling cup 80x80x32mm



**00-01200, F**  
Accessory for gear-tray  
release



**00-20101, W**  
2xend cap - metal, 5-  
conductor terminal box,  
grommet; Lipo80/Lina80



**00-20103, W**  
2xend cap - plastic, 5-  
conductor terminal box,  
grommet; Lipo80/Lina80



**00-20700, W**  
2 pcs of wall fastening  
Lipo/Lina



**00-51300, W**  
set for suspension into  
3-phase track, non-  
dimmable luminaires