



## Luminaire

# Lina80-S

11S-531M-50GED/830, S



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



|                                   |                         |
|-----------------------------------|-------------------------|
| Type of installation              | Suspended               |
| Light distribution                | Direct-indirect         |
| Luminaire shape                   | Linear                  |
| Colour of the luminaires          | Silver                  |
| Material                          | Aluminium               |
| Lifetime                          | L90/B50 50 000 hours    |
| Warranty                          | 60 months               |
| Description of luminaires         | Luminaire suspended     |
| Dimensions                        | 2810 mm × 80 mm × 93 mm |
| Type of optical system            | Matt parabolic louvre   |
| Luminous flux                     | 11876 lm ± 10 %         |
| Colour Temperature                | 3000 K warm white       |
| Luminous efficacy                 | 119 lm/W                |
| MacAdam Light source              | 2                       |
| Colour rendering index            | 80                      |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 16.2                    |
| Luminaire power input             | 100 W ± 10 %            |
| Connection of the luminaires      | DALI dimmable           |
| Electrical voltage                | 220-240V                |
| Frequency                         | 50/60Hz                 |

⊕ CE IP 20

## Downloads

Installation instructions



Photos

