


Luminaire

Zuli

121-200I-20GGM/830, S


Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

Technical drawing


| | |
|-----------------------------------|--------------------------|
| Type of installation | Surface |
| Light distribution | Direct |
| Luminaire shape | Angular |
| Colour of the luminaires | Silver |
| Material | Aluminium |
| Lifetime | L80/B20 50 000 hours |
| Warranty | 5 years |
| Description of luminaires | Luminaire surface |
| Dimensions | 1145 mm × 125 mm × 50 mm |
| Light source | LED MODUL |
| Type of optical system | Microprisma |
| Luminous flux* | 2700 lm |
| Colour Temperature | 3000 K warm white |
| Luminous efficacy | 110 lm/W |
| MacAdam Light source | 2 |
| Colour rendering index | 80 |
| UGR max. X=4H Y=8H, ρ=70,50,20 | 18.7 |

Curve



Luminaire power input* 24.5 W

Connection of the luminaires ON/OFF + 1h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

* $\pm 10\%$

Downloads

Installation instructions



Photos

