


**Luminaire**

# Zuli

**121-200I-30GED/840, S**


Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

**Technical drawing**


|                                   |                             |
|-----------------------------------|-----------------------------|
| Type of installation              | Surface, Suspended          |
| Light distribution                | Direct                      |
| Luminaire shape                   | Angular                     |
| Colour of the luminaires          | Silver                      |
| Material                          | Aluminium                   |
| Lifetime                          | L80/B20 50 000 hours        |
| Warranty                          | 5 years                     |
| Description of luminaires         | Luminaire surface/suspended |
| Dimensions                        | 1705 mm × 125 mm × 50 mm    |
| Light source                      | LED MODUL                   |
| Type of optical system            | Microprisma                 |
| Luminous flux*                    | 2760 lm                     |
| Colour Temperature                | 4000 K cool white           |
| Luminous efficacy                 | 127 lm/W                    |
| MacAdam Light source              | 2                           |
| Colour rendering index            | 80                          |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 17.3                        |

Luminaire power input\* 21.8 W

---

Connection of the luminaires DALI

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos

