



## Luminaire

# Zuli

121-200K-30GGE/840, W



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

## Technical drawing



|                           |                             |
|---------------------------|-----------------------------|
| Type of installation      | Surface, Suspended          |
| Light distribution        | Direct                      |
| Colour of the luminaires  | White                       |
| Material                  | Aluminium                   |
| Lifetime                  | L80/B20 50 000 hours        |
| Warranty                  | 60 months                   |
| Description of luminaires | Luminaire surface/suspended |

|              |                          |
|--------------|--------------------------|
| Dimensions   | 1705 mm × 125 mm × 50 mm |
| Light source | LED MODUL                |

|                        |               |
|------------------------|---------------|
| Type of optical system | Opal diffuser |
|------------------------|---------------|

|               |                |
|---------------|----------------|
| Luminous flux | 6470 lm ± 10 % |
|---------------|----------------|

|                    |                   |
|--------------------|-------------------|
| Colour Temperature | 4000 K cool white |
|--------------------|-------------------|

|                   |          |
|-------------------|----------|
| Luminous efficacy | 138 lm/W |
|-------------------|----------|

|                      |   |
|----------------------|---|
| MacAdam Light source | 2 |
|----------------------|---|

|                        |    |
|------------------------|----|
| Colour rendering index | 80 |
|------------------------|----|

|                       |               |
|-----------------------|---------------|
| Luminaire power input | 46.9 W ± 10 % |
|-----------------------|---------------|

|                              |                                 |
|------------------------------|---------------------------------|
| Connection of the luminaires | Electronic ballast non-dimmable |
|------------------------------|---------------------------------|

|                    |          |
|--------------------|----------|
| Electrical voltage | 220-240V |
|--------------------|----------|

|           |         |
|-----------|---------|
| Frequency | 50/60Hz |
|-----------|---------|

⊥ CE IP 20

## Downloads

Installation instructions



Photos

