



Luminaire

Zuli

121-200K-40GGD/840, S



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

Technical drawing



Type of installation	Surface, Suspended
Light distribution	Direct
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	60 months
Description of luminaires	Luminaire surface/suspended

Dimensions	2265 mm × 125 mm × 50 mm
Light source	LED MODUL

Type of optical system	Opal diffuser
------------------------	---------------

Luminous flux	8630 lm ± 10 %
---------------	----------------

Colour Temperature	4000 K cool white
--------------------	-------------------

Luminous efficacy	138 lm/W
-------------------	----------

MacAdam Light source	2
----------------------	---

Colour rendering index	80
------------------------	----

Luminaire power input	62.6 W ± 10 %
-----------------------	---------------

Connection of the luminaires	DALI dimmable
------------------------------	---------------

Electrical voltage	220-240V
--------------------	----------

Frequency	50/60Hz
-----------	---------

⊥ CE IP 20

Downloads

Installation instructions



Photos

