



## Luminaire


# Zuli

121-301K-10GED/830, B



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

## Technical drawing



|  |                         |
|--|-------------------------|
| Type of installation                   | Wall mounted            |
| Light distribution                     | Direct-indirect         |
| Luminaire shape                        | Angular                 |
| Colour of the luminaires               | Black                   |
| Material                               | Aluminium               |
| Lifetime                               | L80/B10 50 000 hours    |
| Warranty                               | 5 years                 |
| Description of luminaires              | Luminaire wall mounted  |
| Dimensions                             | 590 mm × 125 mm × 50 mm |
| Weight                                 | 1.9 kg                  |
| Light source                           | LED MODUL               |
| Type of optical system                 | Opal diffuser           |
| Luminous flux*                         | 2000 lm                 |
| Colour Temperature                     | 3000 K warm white       |
| Luminous efficacy                      | 123 lm/W                |
| MacAdam Light source                   | 2                       |
| Colour rendering index                 | 80                      |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 17.9                    |

Luminaire power input\* 16.2 W

---

Connection of the luminaires DALI

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos

