


**Luminaire**

# Zuli

121-500K-25GGM/840, S



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

**Technical drawing**


|                                   |                          |
|-----------------------------------|--------------------------|
| Type of installation              | Suspended                |
| Light distribution                | Direct                   |
| Luminaire shape                   | Angular                  |
| Colour of the luminaires          | Silver                   |
| Material                          | Aluminium                |
| Lifetime                          | L80/B20 50 000 hours     |
| Warranty                          | 60 months                |
| Description of luminaires         | Luminaire suspended      |
| Dimensions                        | 1425 mm × 125 mm × 50 mm |
| Light source                      | LED MODUL                |
| Type of optical system            | Opal diffuser            |
| Luminous flux                     | 5390 lm ± 10 %           |
| Colour Temperature                | 4000 K cool white        |
| Luminous efficacy                 | 138 lm/W                 |
| MacAdam Light source              | 2                        |
| Colour rendering index            | 80                       |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 24.2                     |

## Curve



Luminaire power input 39.1 W ± 10 %

Connection of the luminaires Electronic ballast non-dimmable with 1h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

## Downloads

Installation instructions



Photos

