



Luminaire

Zuli

121-500K-30GGD/830, W



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

Technical drawing



| | |
|------------------------------|--------------------------|
| Type of installation | Suspended |
| Light distribution | Direct |
| Colour of the luminaires | White |
| Material | Aluminium |
| Lifetime | L80/B20 50 000 hours |
| Warranty | 60 months |
| Description of luminaires | Luminaire suspended |
| Dimensions | 1705 mm × 125 mm × 50 mm |
| Light source | LED MODUL |
| Type of optical system | Opal diffuser |
| Luminous flux | 6160 lm ± 10 % |
| Colour Temperature | 3000 K warm white |
| Luminous efficacy | 131 lm/W |
| MacAdam Light source | 2 |
| Colour rendering index | 80 |
| Luminaire power input | 46.9 W ± 10 % |
| Connection of the luminaires | DALI dimmable |
| Electrical voltage | 220-240V |
| Frequency | 50/60Hz |

⊕ CE IP 20

Downloads

Installation instructions



Photos

