



## Luminaire

# Zuli

121-500K-40GGD/830, S



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

## Technical drawing



|                              |                          |
|------------------------------|--------------------------|
| Type of installation         | Suspended                |
| Light distribution           | Direct                   |
| Colour of the luminaires     | Silver                   |
| Material                     | Aluminium                |
| Lifetime                     | L80/B20 50 000 hours     |
| Warranty                     | 5 years                  |
| Description of luminaires    | Luminaire suspended      |
| Dimensions                   | 2265 mm × 125 mm × 50 mm |
| Light source                 | LED MODUL                |
| Type of optical system       | Opal diffuser            |
| Luminous flux*               | 8220 lm                  |
| Colour Temperature           | 3000 K warm white        |
| Luminous efficacy            | 131 lm/W                 |
| MacAdam Light source         | 2                        |
| Colour rendering index       | 80                       |
| Luminaire power input*       | 62.6 W                   |
| Connection of the luminaires | DALI                     |
| Electrical voltage           | 220-240V                 |
| Frequency                    | 50/60Hz                  |

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos

