



## Luminaire

# Zuli-S

121S-500K-20GEE/830, B



We realize that there is beauty in simplicity, so we have created our Zuli-S system luminaire. The Zuli-S luminaire is based on the timeless shape that everyone has known for many years. The luminaires come with a very efficient LED light source, thanks to which the luminaires have a very high economical and, last but not least, ecological value, as they require a relatively small amount of energy. Zuli-S luminaires can be fitted with a parabolic louver made of polished aluminium sheet or an opal diffuser.

## Technical drawing



|                           |                          |
|---------------------------|--------------------------|
| Type of installation      | Suspended                |
| Light distribution        | Direct                   |
| Colour of the luminaires  | Black                    |
| Material                  | Aluminium                |
| Lifetime                  | L80/B20 50 000 hours     |
| Warranty                  | 60 months                |
| Description of luminaires | Luminaire suspended      |
| Dimensions                | 1135 mm × 125 mm × 50 mm |
| Weight                    | 3.2 kg                   |
| Light source              | LED MODUL                |

|                        |                   |
|------------------------|-------------------|
| Type of optical system | Opal diffuser     |
| Luminous flux          | 2990 lm ± 10 %    |
| Colour Temperature     | 3000 K warm white |
| Luminous efficacy      | 140 lm/W          |
| MacAdam Light source   | 2                 |
| Colour rendering index | 80                |

|                              |                                 |
|------------------------------|---------------------------------|
| Luminaire power input        | 21.4 W ± 10 %                   |
| Connection of the luminaires | Electronic ballast non-dimmable |
| Electrical voltage           | 220-240V                        |
| Frequency                    | 50/60Hz                         |

 **CE** IP 20

# Curve



## Downloads

Installation instructions



Photos



**Accessories**

**00-00352, K**  
 cable 3x0,75 2000mm

**00-00355, K**  
 cable 5x0,75 2000mm

**00-00356, K**  
 cable 5x0,75 4000mm

**00-00358, K**  
 cable 3x0,75 4000mm

**00-00360, K**  
 cable 3x0,75 6000mm

**00-00363, K**  
 cable 5x1,5 2000mm

**00-00364, K**  
 cable 5x1,5 4000mm

**00-00365, K**  
 cable 5x1,5 6000mm

**00-00370, S**  
 ceiling cup 80x80x32mm

**121-00200, N**  
 straight connector

**121-00300, N**  
 wire suspension  
 2000mm

**121-00301, N**  
 wire suspension  
 4000mm

**121-00302, N**  
 wire suspension  
 6000mm

**121-20101, B**  
 2xend cap - plastic