



## Luminaire

# Zuli-S

121S-501I-40GEM/830, B



We realize that there is beauty in simplicity, so we have created our Zuli-S system luminaire. The Zuli-S luminaire is based on the timeless shape that everyone has known for many years. The luminaires come with a very efficient LED light source, thanks to which the luminaires have a very high economical and, last but not least, ecological value, as they require a relatively small amount of energy. Zuli-S luminaires can be fitted with a parabolic louver made of polished aluminium sheet or an opal diffuser.

## Technical drawing



|                                   |   |
|-----------------------------------|---|
| Type of installation              | Suspended   |
| Light distribution                | Direct-indirect                                   |
| Colour of the luminaires          | Black   |
| Material                          | Aluminium   |
| Lifetime                          | L80/B20 50 000 hours                              |
| Warranty                          | 60 months   |
| Description of luminaires         | Luminaire suspended                               |
| Dimensions                        | 2255 mm × 125 mm × 50 mm                          |
| Light source                      | LED MODUL   |
| Type of optical system            | Microprisma                                       |
| Luminous flux                     | 6400 lm ± 10 %                                    |
| Colour Temperature                | 3000 K warm white                                 |
| Luminous efficacy                 | 126 lm/W  |
| MacAdam Light source              | 2   |
| Colour rendering index            | 80  |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 13.7  |
| Luminaire power input             | 50.9 W ± 10 %                                     |
| Connection of the luminaires      | Electronic ballast non-dimmable with 1h emergency |
| Electrical voltage                | 220-240V  |
| Frequency                         | 50/60Hz   |

⊕ CE IP 20

# Curve



## Downloads

Installation instructions



Photos



**Accessories**

**00-00352, K**  
 cable 3x0,75 2000mm

**00-00355, K**  
 cable 5x0,75 2000mm

**00-00356, K**  
 cable 5x0,75 4000mm

**00-00358, K**  
 cable 3x0,75 4000mm

**00-00360, K**  
 cable 3x0,75 6000mm

**00-00363, K**  
 cable 5x1,5 2000mm

**00-00364, K**  
 cable 5x1,5 4000mm

**00-00365, K**  
 cable 5x1,5 6000mm

**00-00370, S**  
 ceiling cup 80x80x32mm

**121-00200, N**  
 straight connector

**121-00300, N**  
 wire suspension  
 2000mm

**121-00301, N**  
 wire suspension  
 4000mm

**121-00302, N**  
 wire suspension  
 6000mm

**121-20101, B**  
 2xend cap - plastic