



## Luminaire

# Zuli-S

121S-531M-20GEE/830, S



We realize that there is beauty in simplicity, so we have created our Zuli-S system luminaire. The Zuli-S luminaire is based on the timeless shape that everyone has known for many years. The luminaires come with a very efficient LED light source, thanks to which the luminaires have a very high economical and, last but not least, ecological value, as they require a relatively small amount of energy. Zuli-S luminaires can be fitted with a parabolic louver made of polished aluminium sheet or an opal diffuser.

## Technical drawing



|                                        |                          |
|----------------------------------------|--------------------------|
| Type of installation                   | Suspended                |
| Light distribution                     | Direct-indirect          |
| Luminaire shape                        | Angular                  |
| Colour of the luminaires               | Silver                   |
| Material                               | Aluminium                |
| Lifetime                               | L80/B20 50 000 hours     |
| Warranty                               | 60 months                |
| Description of luminaires              | Luminaire suspended      |
| Dimensions                             | 1135 mm × 125 mm × 50 mm |
| Weight                                 | 3.3 kg                   |
| Light source                           | LED MODUL                |
| Type of optical system                 | Matt parabolic louvre    |
| Luminous flux                          | 4110 lm ± 10 %           |
| Colour Temperature                     | 3000 K warm white        |
| Luminous efficacy                      | 123 lm/W                 |
| MacAdam Light source                   | 2                        |
| Colour rendering index                 | 80                       |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 11.3                     |

## Curve



Luminaire power input 33.4 W ± 10 %

Connection of the luminaires Electronic ballast non-dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

## Downloads

Installation instructions



Photos



**Accessories**

**00-00352, K**  
 cable 3x0,75 2000mm

**00-00355, K**  
 cable 5x0,75 2000mm

**00-00356, K**  
 cable 5x0,75 4000mm

**00-00358, K**  
 cable 3x0,75 4000mm

**00-00360, K**  
 cable 3x0,75 6000mm

**00-00363, K**  
 cable 5x1,5 2000mm

**00-00364, K**  
 cable 5x1,5 4000mm

**00-00365, K**  
 cable 5x1,5 6000mm

**00-00370, S**  
 ceiling cup 80x80x32mm

**121-00200, N**  
 straight connector

**121-00300, N**  
 wire suspension  
 2000mm

**121-00301, N**  
 wire suspension  
 4000mm

**121-00302, N**  
 wire suspension  
 6000mm

**121-20101, S**  
 2xend cap - plastic