


**Luminaire**


# Rotao100

127-561I-10GGD/830, B


**Technical drawing**


|  |                      |
|--|----------------------|
| Type of installation                   | Suspended            |
| Light distribution                     | Direct-indirect      |
| Luminaire shape                        | Circular             |
| Colour of the luminaires               | Black                |
| Material                               | Aluminium            |
| Lifetime                               | L80/B20 50 000 hours |
| Warranty                               | 60 months            |
| Description of luminaires              | Luminaire suspended  |
| Dimensions                             | ø 600 mm × 87 mm     |
| Weight                                 | 6.5 kg               |
| Light source                           | LED MODUL            |
| Type of optical system                 | Microprisma          |
| Luminous flux                          | 3350 lm ± 10 %       |
| Colour Temperature                     | 3000 K warm white    |
| Luminous efficacy                      | 86 lm/W              |
| MacAdam Light source                   | 3                    |
| Colour rendering index                 | 80                   |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 17.3                 |

## Curve



Luminaire power input 38.8 W  $\pm$  10 %

Connection of the luminaires DALI dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

  IP 20

## Downloads

Installation instructions



Photos

