


**Luminaire**

# Kvado

14-204I-40GEM/830, B



The Kvado family luminaires are made of a high-quality aluminium profile and are available in versions with both direct and direct-indirect distribution of light. Their simple shape and quality of workmanship make them suitable for any space. The luminaires can combine an opal diffuser or microprismatic optics. Thanks to all this, you can use them in administrative buildings, shopping centres, public spaces or residential buildings. Both pendant and surface versions are available in various colours according to our Halla RAL chart.

**Technical drawing**


Type of installation	Surface, Suspended
Light distribution	Direct
Luminaire shape	Angular
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/suspended
Dimensions	600 mm × 600 mm × 129 mm
Light source	LED MODUL

Type of optical system	Microprisma
Luminous flux*	3880 lm
Colour Temperature	3000 K warm white
Luminous efficacy	107 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	19

Luminaire power input*	36.3 W
Connection of the luminaires	ON/OFF + 1h emergency
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00333, B**  
suspension set  
2000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00340, B**  
suspension set  
4000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00344, B**  
suspension set  
6000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup