



Luminaire

Kvado

14-204K-90GED/840, S



The Kvado family luminaires are made of a high-quality aluminium profile and are available in versions with both direct and direct-indirect distribution of light. Their simple shape and quality of workmanship make them suitable for any space. The luminaires can combine an opal diffuser or microprismatic optics. Thanks to all this, you can use them in administrative buildings, shopping centres, public spaces or residential buildings. Both pendant and surface versions are available in various colours according to our Halla RAL chart.

Technical drawing



Type of installation	Surface, Suspended
Light distribution	Direct
Luminaire shape	Angular
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/suspended
Dimensions	900 mm × 900 mm × 129 mm
Weight	18.3 kg
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux*	7790 lm
Colour Temperature	4000 K cool white
Luminous efficacy	95 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, $\rho=70,50,20$	20.3

Luminaire power input* 81.6 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

  IP 20

*±10 %

Downloads

Installation instructions



Photos



Accessories



00-00333, S
suspension set
2000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



00-00340, S
suspension set
4000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



00-00344, S
suspension set
6000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup