



Luminaire

Rundo 120

15-290I-10GEE/830, W



Circular luminaires with an aluminium profile with a height of 120 mm and an excellent luminous efficacy of up to 145 lm/W. A Rundo120 has wide range of functions and dimensions with a diameter of up to 1150 mm. These surface or pendant luminaires can be used as basic lighting features in commercial and residential spaces. Thanks to sophisticated technology, the luminaires do not cause glare and the lighting can be adapted to smaller or large commercial spaces. You can choose between a version with an opal diffuser made of PMMA or a microprismatic optical system.

Technical drawing



| | |
|------------------------------|----------------------|
| Type of installation | Surface |
| Light distribution | Direct |
| Luminaire shape | Circular |
| Colour of the luminaires | White |
| Material | Aluminium |
| Lifetime | L80/B10 50 000 hours |
| Warranty | 5 years |
| Description of luminaires | Luminaire surface |
| Dimensions | ø 950 mm × 120 mm |
| Type of optical system | Microprisma |
| Luminous flux* | 6670 lm |
| Colour Temperature | 3000 K warm white |
| Luminous efficacy | 91 lm/W |
| MacAdam Light source | 2 |
| Colour rendering index | 80 |
| Luminaire power input* | 73.6 W |
| Connection of the luminaires | ON/OFF |
| Electrical voltage | 220-240V |
| Frequency | 50/60Hz |

⊕ CE IP 20

*±10 %

Curve



