



Luminaire

Rundo 120

15-5B0I-10GEM/830, W



Circular luminaires with an aluminium profile with a height of 120 mm and an excellent luminous efficacy of up to 145 lm/W. A Rundo120 has wide range of functions and dimensions with a diameter of up to 1150 mm. These surface or pendant luminaires can be used as basic lighting features in commercial and residential spaces. Thanks to sophisticated technology, the luminaires do not cause glare and the lighting can be adapted to smaller or large commercial spaces. You can choose between a version with an opal diffuser made of PMMA or a microprismatic optical system.

Technical drawing



Type of installation Suspended

Light distribution Direct

Luminaire shape Circular

Colour of the luminaires White

Material Aluminium

Lifetime L80/B10 50 000 hours

Warranty 5 years

Description of luminaires Luminaire suspended

Dimensions ø 1240 mm × 120 mm

Type of optical system Microprisma

Luminous flux* 8690 lm

Colour Temperature 3000 K warm white

Luminous efficacy 92 lm/W

MacAdam Light source 2

Colour rendering index 80

Luminaire power input* 94 W

Connection of the luminaires ON/OFF + 1h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

*±10 %

Curve



