


**Luminaire**

# Burbu

19-205I-40GED/840, S



In the Burbu family, we round off squares with corners and we make ovals from rectangles. These luminaires with a 70 mm profile height have a positive and pleasant effect in the room. Combine luminaires with different diameters and different hanging possibilities. In a range of colours and power versions, flush-mount, wall and pendant models, the Burbu family of luminaires are ideal for hotel lobbies, entrance halls, offices, shops and households.

**Technical drawing**


|  |  |
|--|--|
| Type of installation                   | Surface, Wall mounted, Suspended         |
| Light distribution                     | Direct                                   |
| Luminaire shape                        | Rounded                                  |
| Colour of the luminaires               | Silver                                   |
| Material                               | Aluminium                                |
| Lifetime                               | L80/B20 50 000 hours                     |
| Warranty                               | 60 months                                |
| Description of luminaires              | Luminaire surface/wall mounted/suspended |
| Dimensions                             | 1222 mm × 155 mm × 70 mm                 |
| Weight                                 | 5.9 kg                                   |
| Light source                           | LED MODUL                                |
| Type of optical system                 | Microprisma                              |
| Luminous flux                          | 3450 lm ± 10 %                           |
| Colour Temperature                     | 4000 K cool white                        |
| Luminous efficacy                      | 92 lm/W                                  |
| MacAdam Light source                   | 3  |
| Colour rendering index                 | 80                                       |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 18.9                                     |

Luminaire power input 37.6 W  $\pm$  10 %

---

Connection of the luminaires DALI dimmable

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

 **CE** IP 20

## Downloads

Installation instructions



Photos



## Accessories



**00-00333, S**  
suspension set  
2000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**19-0009, S**  
Mounting distance kit for square  
luminaire, circular 370 mm