



## Luminaire

# Burbu

19-205I-50GEM/830, W



In the Burbu family, we round off squares with corners and we make ovals from rectangles. These luminaires with a 70 mm profile height have a positive and pleasant effect in the room. Combine luminaires with different diameters and different hanging possibilities. In a range of colours and power versions, flush-mount, wall and pendant models, the Burbu family of luminaires are ideal for hotel lobbies, entrance halls, offices, shops and households.

## Technical drawing



|                                   |  |
|-----------------------------------|--|
| Type of installation              | Surface, Wall mounted, Suspended         |
| Light distribution                | Direct                                   |
| Luminaire shape                   | Rounded                                  |
| Colour of the luminaires          | White                                    |
| Material                          | Aluminium                                |
| Lifetime                          | L80/B20 50 000 hours                     |
| Warranty                          | 60 months                                |
| Description of luminaires         | Luminaire surface/wall mounted/suspended |
| Dimensions                        | 1522 mm × 155 mm × 70 mm                 |
| Light source                      | LED MODUL                                |
| Type of optical system            | Microprisma                              |
| Luminous flux                     | 4110 lm ± 10 %                           |
| Colour Temperature                | 3000 K warm white                        |
| Luminous efficacy                 | 87 lm/W                                  |
| MacAdam Light source              | 3  |
| Colour rendering index            | 80                                       |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 18.8                                     |

|                              |   |
|------------------------------|---|
| Luminaire power input        | 47 W $\pm$ 10 %                                   |
| Connection of the luminaires | Electronic ballast non-dimmable with 1h emergency |
| Electrical voltage           | 220-240V  |
| Frequency                    | 50/60Hz   |

 **CE** IP 20

## Downloads

Installation instructions



Photos



## Accessories



**00-00333, W**  
suspension set  
2000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**19-0009, W**  
Mounting distance kit for square  
luminaire, circular 370 mm