



Luminaire


Burbu

19-214K-40GED/840, W



In the Burbu family, we round off squares with corners and we make ovals from rectangles. These luminaires with a 70 mm profile height have a positive and pleasant effect in the room. Combine luminaires with different diameters and different hanging possibilities. In a range of colours and power versions, flush-mount, wall and pendant models, the Burbu family of luminaires are ideal for hotel lobbies, entrance halls, offices, shops and households.

Technical drawing



Type of installation	Surface, Wall mounted, Suspended
Light distribution	Direct
Luminaire shape	Rounded
Colour of the luminaires	White
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	60 months
Description of luminaires	Luminaire surface/wall mounted/suspended
Dimensions	600 mm × 600 mm × 70 mm
Weight	7.1 kg
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux	4680 lm ± 10 %
Colour Temperature	4000 K cool white
Luminous efficacy	137 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, $\rho=70,50,20$	21.5

Luminaire power input 34.1 W \pm 10 %

Connection of the luminaires DALI dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

 **CE** IP 20

Downloads

Installation instructions



Photos



Accessories




00-00333, W
suspension set
2000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



00-00340, W
suspension set
4000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



00-00344, W
suspension set
6000mm, 4 pcs.of wires,
cable 5x0,75mm, ceiling
cup



19-0009, W
Mounting distance kit for square
luminaire, circular 370 mm