



## Luminaire

# Burbu

19-214K-40GEE/840, S



In the Burbu family, we round off squares with corners and we make ovals from rectangles. These luminaires with a 70 mm profile height have a positive and pleasant effect in the room. Combine luminaires with different diameters and different hanging possibilities. In a range of colours and power versions, flush-mount, wall and pendant models, the Burbu family of luminaires are ideal for hotel lobbies, entrance halls, offices, shops and households.

## Technical drawing



|  |  |
|--|--|
| Type of installation                   | Surface, Wall mounted, Suspended         |
| Light distribution                     | Direct                                   |
| Luminaire shape                        | Rounded                                  |
| Colour of the luminaires               | Silver                                   |
| Material                               | Aluminium                                |
| Lifetime                               | L80/B20 50 000 hours                     |
| Warranty                               | 5 years                                  |
| Description of luminaires              | Luminaire surface/wall mounted/suspended |
| Dimensions                             | 600 mm × 600 mm × 70 mm                  |
| Weight                                 | 7 kg                                     |
| Light source                           | LED MODUL                                |
| Type of optical system                 | Opal diffuser                            |
| Luminous flux*                         | 4680 lm                                  |
| Colour Temperature                     | 4000 K cool white                        |
| Luminous efficacy                      | 137 lm/W                                 |
| MacAdam Light source                   | 3  |
| Colour rendering index                 | 80                                       |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 21.5                                     |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 34.1 W   |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

   IP 20

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00333, S**  
suspension set  
2000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00340, S**  
suspension set  
4000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00344, S**  
suspension set  
6000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**19-0009, S**  
Mounting distance kit for square  
luminaire, circular 370 mm