


**Luminaire**

# Rundo

**190-240I-10GGM3I/840, B**


Circular luminaires with an aluminium profile come in two heights, 62 mm and 87 mm. Rundo luminaires feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Rundo luminaires with a diameter of up to 1150 mm can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

Type of installation	Surface, Wall mounted
Light distribution	Direct
Luminaire shape	Circular
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	24 months
Description of luminaires	Luminaire surface/wall mounted
Dimensions	ø 400 mm × 62 mm
Light source	LED MODUL
Type of optical system	Microprisma
Luminous flux	2500 lm ± 10 %
Colour Temperature	4000 K cool white
Luminous efficacy	97 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	19

## Technical drawing



Luminaire power input 25.8 W  $\pm$  10 %

Connection of the luminaires Electronic ballast non-dimmable, multiwatt with 3h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

  IP 40

## Curve



## Downloads

Installation instructions



Photos

