



## Luminaire

# Rundo 62

190-241I-10GGMI/830, S



Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

## Technical drawing



|   |                                     |
|---|-------------------------------------|
| Type of installation                      | Surface, Wall mounted               |
| Light distribution                        | Direct-indirect                     |
| Luminaire shape                           | Circular                            |
| Colour of the luminaires                  | Silver                              |
| Material                                  | Aluminium                           |
| Lifetime                                  | L80/B20 50 000 hours                |
| Warranty                                  | 60 months                           |
| Description of luminaires                 | Luminaire surface/wall mounted      |
| Dimensions                                | $\varnothing$ 400 mm $\times$ 62 mm |
| Weight                                    | 3.9 kg                              |
| Light source                              | LED MODUL                           |
| Type of optical system                    | Microprisma                         |
| Luminous flux                             | 3000 lm $\pm$ 10 %                  |
| Colour Temperature                        | 3000 K warm white                   |
| Luminous efficacy                         | 103 lm/W                            |
| MacAdam Light source                      | 3                                   |
| Colour rendering index                    | 80                                  |
| UGR max. X=4H<br>Y=8H, $\varrho=70,50,20$ | 16.2                                |

## Curve



Luminaire power input 29.2 W  $\pm$  10 %

Connection of the luminaires Electronic ballast non-dimmable, multiwatt with 1h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

