


**Luminaire**

# Rundo 62

190-281K-10GEE/830, B +  
00-00384-1000/RUN, B



Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

|                           |                      |
|---------------------------|----------------------|
| Type of installation      | Suspended            |
| Light distribution        | Direct-indirect      |
| Luminaire shape           | Circular             |
| Colour of the luminaires  | Black                |
| Material                  | Aluminium            |
| Lifetime                  | L90/B50 50 000 hours |
| Warranty                  | 60 months            |
| Description of luminaires | Luminaire suspended  |
| Dimensions                | ø 850 mm × 62 mm     |
| Light source              | LED MODUL            |

|                                   |                   |
|-----------------------------------|-------------------|
| Type of optical system            | Opal diffuser     |
| Luminous flux                     | 6390 lm ± 10 %    |
| Colour Temperature                | 3000 K warm white |
| Luminous efficacy                 | 131 lm/W          |
| MacAdam Light source              | 3                 |
| Colour rendering index            | 80                |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 20                |

Luminaire power input 48.9 W  $\pm$  10 %

---

Connection of the luminaires Electronic ballast non-dimmable

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

 **CE** IP 40

