



## Luminaire

# Gatu

21-001F-20GJV/M/840, S +  
00-00152M3



If we combine a simple design with advanced functionality, we get the luminaires of Gatu family. The recessed luminaire with an adjustable reflector can be aimed at the required object. In addition to high-brightness LEDs with colour rendering of  $Ra > 80$  or  $Ra > 90$ , the luminaire also contains a wide range of light sources. The RealWhite technology highlights the white, StrongColour highlights the selected colour, and RealColour with an extremely high colour rendering of  $Ra > 97$  emphasizes the object's own colour. The illuminated object thus looks even more appealing, which makes Gatu luminaires suitable for commercial and cultural spaces, car showrooms and shop windows.

## Technical drawing



|                              |   |
|------------------------------|---|
| Type of installation         | Recessed  |
| Light distribution           | Direct  |
| Luminaire shape              | Angular   |
| Colour of the luminaires     | Silver  |
| Material                     | Sheet metal                                       |
| Lifetime                     | L80/B10 50 000 hours                              |
| Warranty                     | 60 months   |
| Description of luminaires    | Luminaire recessed                                |
| Dimensions                   | 350 mm × 185 mm × 100 mm                          |
| Light source                 | LED MODUL   |
| Type of optical system       | Reflector   |
| Luminous flux                | 2190 lm ± 10 %                                    |
| Colour Temperature           | 4000 K cool white                                 |
| Luminous efficacy            | 122 lm/W  |
| MacAdam Light source         | 3   |
| Colour rendering index       | 80  |
| Beam angle                   | 41°   |
| Luminaire power input        | 36 W ± 10 %                                       |
| Connection of the luminaires | Electronic ballast non-dimmable with 3h emergency |
| Electrical voltage           | 220-240V  |
| Frequency                    | 50/60Hz   |

 **CE** IP 20

## Downloads

Installation instructions



Photos

