



## Luminaire

# Gatu

21-001W-10GJV/830, S +  
00-00155EI



If we combine a simple design with advanced functionality, we get the luminaires of Gatu family. The recessed luminaire with an adjustable reflector can be aimed at the required object. In addition to high-brightness LEDs with colour rendering of  $Ra > 80$  or  $Ra > 90$ , the luminaire also contains a wide range of light sources. The RealWhite technology highlights the white, StrongColour highlights the selected colour, and RealColour with an extremely high colour rendering of  $Ra > 97$  emphasizes the object's own colour. The illuminated object thus looks even more appealing, which makes Gatu luminaires suitable for commercial and cultural spaces, car showrooms and shop windows.

## Technical drawing



|                              |  |
|------------------------------|--|
| Type of installation         | Recessed                                   |
| Light distribution           | Direct                                     |
| Luminaire shape              | Angular                                    |
| Colour of the luminaires     | Silver                                     |
| Material                     | Sheet metal                                |
| Lifetime                     | L80/B10 50 000 hours                       |
| Warranty                     | 60 months                                  |
| Description of luminaires    | Luminaire recessed                         |
| Dimensions                   | 185 mm × 185 mm × 100 mm                   |
| Light source                 | LED MODUL                                  |
| Type of optical system       | Reflector                                  |
| Luminous flux                | 4230 lm ± 10 %                             |
| Colour Temperature           | 3000 K warm white                          |
| Luminous efficacy            | 95 lm/W                                    |
| MacAdam Light source         | 3  |
| Colour rendering index       | 80   |
| Beam angle                   | 62°  |
| Luminaire power input        | 44.5 W ± 10 %                              |
| Connection of the luminaires | Electronic ballast non-dimmable, multiwatt |
| Electrical voltage           | 220-240V                                   |
| Frequency                    | 50/60Hz                                    |

 **CE** IP 20

# Curve



## Downloads

Installation instructions



Photos

