



## Luminaire

# Rotao60

227-5D1K-10GGD/830, W



The designer circular luminaire Rotao60 comes in a large number of diameters, thanks to which it fits well into various social and commercial spaces. You can also use it to decorate your living room or a meeting room. If you combine the luminaire with microprismatic optics, its efficacy can be surprising even in an office. Pendant versions of the Rotao60 luminaire with a diameter of up to 800 mm are suspended on suspension wires which converge into a single ceiling cup, while larger diameters are suspended on wires that run perpendicular to the ceiling.

## Technical drawing



|                              |                      |
|------------------------------|----------------------|
| Type of installation         | Suspended            |
| Light distribution           | Direct-indirect      |
| Luminaire shape              | Circular             |
| Colour of the luminaires     | White                |
| Material                     | Aluminium            |
| Lifetime                     | L80/B20 50 000 hours |
| Warranty                     | 5 years              |
| Description of luminaires    | Luminaire suspended  |
| Dimensions                   | ø 2050 mm × 65 mm    |
| Weight                       | 15.9 kg              |
| Light source                 | LED MODUL            |
| Type of optical system       | Opal diffuser        |
| Luminous flux                | 16270 lm ± 10 %      |
| Colour Temperature           | 3000 K warm white    |
| Luminous efficacy            | 110 lm/W             |
| MacAdam Light source         | 3                    |
| Colour rendering index       | 80                   |
| Luminaire power input        | 148.3 W ± 10 %       |
| Connection of the luminaires | DALI dimmable        |
| Electrical voltage           | 220-240V             |
| Frequency                    | 50/60Hz              |

 **CE** IP 20

## Downloads

Installation instructions



Photos

