



## Luminaire

# Rotao60

227-5F1I-10GED/840, B



The designer circular luminaire Rotao60 comes in a large number of diameters, thanks to which it fits well into various social and commercial spaces. You can also use it to decorate your living room or a meeting room. If you combine the luminaire with microprismatic optics, its efficacy can be surprising even in an office. Pendant versions of the Rotao60 luminaire with a diameter of up to 800 mm are suspended on suspension wires which converge into a single ceiling cup, while larger diameters are suspended on wires that run perpendicular to the ceiling.

## Technical drawing



|                           |                      |
|---------------------------|----------------------|
| Type of installation      | Suspended            |
| Light distribution        | Direct-indirect      |
| Luminaire shape           | Circular             |
| Colour of the luminaires  | Black                |
| Material                  | Aluminium            |
| Lifetime                  | L80/B20 50 000 hours |
| Warranty                  | 5 years              |
| Description of luminaires | Luminaire suspended  |
| Dimensions                | ø 2980 mm × 65 mm    |
| Light source              | LED MODUL            |

|                        |                   |
|------------------------|-------------------|
| Type of optical system | Microprisma       |
| Luminous flux          | 12800 lm ± 10 %   |
| Colour Temperature     | 4000 K cool white |
| Luminous efficacy      | 84 lm/W           |
| MacAdam Light source   | 3                 |
| Colour rendering index | 80                |

|                              |                |
|------------------------------|----------------|
| Luminaire power input        | 152.8 W ± 10 % |
| Connection of the luminaires | DALI dimmable  |
| Electrical voltage           | 220-240V       |
| Frequency                    | 50/60Hz        |

  IP 20

## Downloads

Installation instructions



Photos

