



## Luminaire

# Flumo60-S

228S-X0XK-XXGXE/830, W



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

|                                   |                         |
|-----------------------------------|-------------------------|
| Type of installation              | Suspended               |
| Light distribution                | Direct                  |
| Luminaire shape                   | Other shape             |
| Colour of the luminaires          | White                   |
| Material                          | Aluminium               |
| Lifetime                          | L80/B20 50 000 hours    |
| Warranty                          | 5 years                 |
| Description of luminaires         | Luminaire suspended     |
| Dimensions                        | 1700 mm × 60 mm × 65 mm |
| Type of optical system            | Opal diffuser           |
| Luminous flux*                    | 905 lm - 4980 lm        |
| Colour Temperature                | 3000 K warm white       |
| Luminous efficacy                 | 119 lm/W                |
| MacAdam Light source              | 3                       |
| Colour rendering index            | 80                      |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 99                      |
| Luminaire power input*            | 7.6 W - 43 W            |
| Connection of the luminaires      | ON/OFF                  |
| Electrical voltage                | 220-240V                |
| Frequency                         | 50/60Hz                 |

 **CE** IP 20

\*±10 %

## Downloads

Installation instructions



Photos

