



## Luminaire

# Sineli

230-781I-15GHT/830, W



Ordinary free standing luminaires have long been out of the game. We have designed and developed an ideal designer luminaire of the Sineli family, which will provide you with comfort at work and will improve your concentration. The Sineli luminaires are designed for both table mounting and free standing, so you can move them freely at any time, thus adapting the arrangement of the items in the room according to your needs. Sturdy construction and weight prevent accidental tipping over and ensure reliable stability. The shape of Sineli resembles a spaceship arriving from a distant galaxy, which can make your office, meeting room or private apartment look more impressive.

## Technical drawing



|                                   |   |
|-----------------------------------|---|
| Type of installation              | Free-standing   |
| Light distribution                | Direct-indirect                                       |
| Luminaire shape                   | Angular   |
| Colour of the luminaires          | White   |
| Material                          | Aluminium   |
| Lifetime                          | L80/B20 50 000 hours                                  |
| Warranty                          | 5 years   |
| Description of luminaires         | Luminaire free-standing                               |
| item description                  | free-standing luminaire HO; flexible cord CH + button |
| Dimensions                        | 920 mm × 360 mm × 2100 mm                             |
| Light source                      | LED MODUL   |
| Type of optical system            | Microprisma   |
| Luminous flux*                    | 8670 lm   |
| Colour Temperature                | 3000 K warm white                                     |
| Luminous efficacy                 | 133 lm/W  |
| MacAdam Light source              | 3   |
| Colour rendering index            | 80  |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 17.1  |

## Curve



Luminaire power input\* 65.3 W

Connection of the luminaires Other type of dimming

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos

