


**Luminaire**


# Stan

**245-781I-20GGT/840, B**


The Stan luminaire with direct and direct-indirect distribution of light has been designed for comfortable and efficient work. It excels not only in its technical parameters, but also the narrow profile of the head itself, thanks to which the luminaire looks decent, professional and can easily blend in with the surroundings. The luminaire is fitted with an optical element consisting of a combination of optical lenses and a plastic parabolic louver, thanks to which the optical materials are not visible and therefore the luminaire does not dazzle. The louver comes in both the basic matt black and matt white colours. The luminaires of the Stan family are designed for both table mounting and free standing, so you can move them freely at any time, thus adapting the arrangement of the items in the room according to your needs.

Type of installation	Free-standing
Light distribution	Direct-indirect
Luminaire shape	Angular
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	60 months
Description of luminaires	Luminaire free-standing
item description	free-standing luminaire ; flexible cord CH + button
Dimensions	1185 mm × 47 mm × 2130 mm
Light source	LED MODUL
Type of optical system	Microprisma
Luminous flux	5500 lm ± 10 %
Colour Temperature	4000 K cool white
Luminous efficacy	83 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	18.5

## Technical drawing



Luminaire power input 66 W  $\pm$  10 %


Connection of the luminaires By switch dimmable (touch dimm)

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

## Curve



## Downloads

Installation instructions



Photos

