



## Luminaire

# Shift

26-100U-10GGV/M/830, W +  
00-00151M3



Designer Kryštof Nosál has created a luminaire with unrivalled variability. In addition, the Shift family of single luminaires allows for any method of installation. You can choose between a semi-recessed, surface and pendant version. The spot LED luminaire consists of 1, 2, 3 or 5 light sources, which can be moved along the axis of the luminaire body, tilted up to an angle of 45° and rotated up to 355°. The luminaire has 4 beam angles of 15°, 25°, 36°, 60°.

Design Kryštof Nosál

## Technical drawing



|                           |                         |
|---------------------------|-------------------------|
| Type of installation      | Recessed                |
| Light distribution        | Direct                  |
| Luminaire shape           | Circular                |
| Colour of the luminaires  | White                   |
| Material                  | Aluminium               |
| Lifetime                  | L80/B20 50 000 hours    |
| Warranty                  | 60 months               |
| Description of luminaires | Luminaire semi-recessed |
| Dimensions                | ø 95 mm × 50 mm         |
| Light source              | LED MODUL               |

|                        |                   |
|------------------------|-------------------|
| Luminous flux          | 1040 lm ± 10 %    |
| Colour Temperature     | 3000 K warm white |
| Luminous efficacy      | 108 lm/W          |
| MacAdam Light source   | 3                 |
| Colour rendering index | 90                |
| Beam angle             | 25°               |

|                              |   |
|------------------------------|---|
| Luminaire power input        | 9.6 W ± 10 %                                      |
| Connection of the luminaires | Electronic ballast non-dimmable with 3h emergency |
| Electrical voltage           | 220-240V  |
| Frequency                    | 50/60Hz   |

  IP 20

# Curve



## Downloads

Installation instructions



Photos



**Accessories**

**00-01000**  
reflector 18°



**00-01001**  
reflector 25°



**00-01002**  
reflector 32°



**00-01003**  
reflector 52°



**00-01100**  
Satinice diffuser