



Luminaire

Shift

26-200S-50GDD/940, W



Designer Kryštof Nosál has created a luminaire with unrivalled variability. In addition, the Shift family of single luminaires allows for any method of installation. You can choose between a semi-recessed, surface and pendant version. The spot LED luminaire consists of 1, 2, 3 or 5 light sources, which can be moved along the axis of the luminaire body, tilted up to an angle of 45° and rotated up to 355°. The luminaire has 4 beam angles of 15°, 25°, 36°, 60°.

Design Kryštof Nosál

Technical drawing



| | |
|---------------------------|-------------------------|
| Type of installation | Surface |
| Light distribution | Direct |
| Luminaire shape | Rounded |
| Colour of the luminaires | White |
| Material | Aluminium |
| Lifetime | L80/B20 50 000 hours |
| Warranty | 60 months |
| Description of luminaires | Luminaire surface |
| Dimensions | 1020 mm × 85 mm × 92 mm |
| Light source | LED MODUL |

| | |
|--|-------------------|
| Type of optical system | Reflector |
| Luminous flux | 1060 lm ± 10 % |
| Colour Temperature | 4000 K cool white |
| Luminous efficacy | 114 lm/W |
| MacAdam Light source | 3 |
| Colour rendering index | 90 |
| Beam angle | 18° |
| UGR max. X=4H Y=8H, $\rho=70,50,20$ | 16.2 |

Curve



Luminaire power input 46.5 W ± 10 %

Connection of the luminaires DALI dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

Downloads

Installation instructions



Photos



Accessories**00-01000**
reflector 18°**00-01001**
reflector 25°**00-01002**
reflector 32°**00-01003**
reflector 52°**00-01100**
Satinice diffuser**00-01101**
Linear optic