


**Luminaire**

# Shift-C

26-500S-10GDD/930, S


**Technical drawing**


|                              |                      |
|------------------------------|----------------------|
| Type of installation         | Suspended            |
| Light distribution           | Direct               |
| Luminaire shape              | Circular             |
| Colour of the luminaires     | Silver               |
| Material                     | Aluminium            |
| Lifetime                     | L80/B20 50 000 hours |
| Warranty                     | 60 months            |
| Description of luminaires    | Luminaire suspended  |
| Dimensions                   | ø 85 mm × 200 mm     |
| Light source                 | LED MODUL            |
| Type of optical system       | Reflector            |
| Luminous flux                | 1000 lm ± 10 %       |
| Colour Temperature           | 3000 K warm white    |
| Luminous efficacy            | 105 lm/W             |
| MacAdam Light source         | 3                    |
| Colour rendering index       | 90                   |
| Beam angle                   | 18°                  |
| Luminaire power input        | 9.5 W ± 10 %         |
| Connection of the luminaires | DALI dimmable        |
| Electrical voltage           | 220-240V             |
| Frequency                    | 50/60Hz              |


**CE** IP 20

# Curve



**Accessories**

**00-01000**  
reflector 18°



**00-01001**  
reflector 25°



**00-01002**  
reflector 32°



**00-01003**  
reflector 52°



**00-01100**  
Satinice diffuser



**00-01101**  
Linear optic