



## Luminaire

# Ravo-C

55-283C-10GDM/830, W



## Technical drawing



Type of installation	Surface, Suspended
Light distribution	Direct
Luminaire shape	Circular
Colour of the luminaires	White
Material	Aluminium/Plastic
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/suspended
Dimensions	ø 172 mm × 187 mm
Light source	LED MODUL

Type of optical system	Clear cover
------------------------	-------------

Luminous flux*	1140 lm
----------------	---------

Colour Temperature	3000 K warm white
--------------------	-------------------

Luminous efficacy	119 lm/W
-------------------	----------

MacAdam Light source	3
----------------------	---

Colour rendering index	80
------------------------	----

Beam angle	62°
------------	-----

UGR max. X=4H Y=8H, $\rho=70,50,20$	18.5
--	------

## Curve



Luminaire power input\* 9.6 W

Connection of the luminaires ON/OFF + 1h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Accessories



**00-00399, W**  
suspension set  
2000mm, 1 pcs.of  
wires, cable  
5x0,75mm, ceiling  
cup