



Luminaire


Ravo-C

55-283K-10GGD/830, S



| | |
|---------------------------|-----------------------------|
| Type of installation | Surface, Suspended |
| Light distribution | Direct |
| Luminaire shape | Circular |
| Colour of the luminaires | Silver |
| Material | Aluminium/Plastic |
| Lifetime | L80/B20 50 000 hours |
| Warranty | 5 years |
| Description of luminaires | Luminaire surface/suspended |
| Dimensions | ø 172 mm × 187 mm |
| Light source | LED MODUL |

Technical drawing



| | |
|--|-------------------|
| Type of optical system | Opal diffuser |
| Luminous flux* | 1830 lm |
| Colour Temperature | 3000 K warm white |
| Luminous efficacy | 102 lm/W |
| MacAdam Light source | 3 |
| Colour rendering index | 80 |
| Beam angle | 64° |
| UGR max. X=4H Y=8H, $\rho=70,50,20$ | 20.6 |

Curve



Luminaire power input* 18 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

*±10 %

Accessories



00-00399, S
suspension set
2000mm, 1 pcs.of
wires, cable
5x0,75mm, ceiling
cup