



## Luminaire

# Ture

56-001K-10GHV/M/830, W +  
00-00152M



It is a circular recessed luminaire of the downlight type with an excellent UGR index <math><19</math> up to 3000 lm, which means that the luminaire does not dazzle. The luminaire is suitable for offices, meeting rooms and, thanks to special sources, also for showrooms. RealWhite highlights the white, StrongColour highlights the selected colour, and RealColour emphasizes the colour of the object. With Tunable White you can set the colour temperature according to the time of day. With the help of these sources, the illuminated objects will look even more attractive. The IP54 class means high level of protection against the penetration of water and foreign matter. Thus, you can use this luminaire even in a demanding environment, such as a wellness centre. Its efficacy is up to 118 lm/W. Ture is available in three versions – a small luminaire with a diameter of 145 mm, a medium luminaire with a diameter of 185 mm and the largest luminaire with a diameter of 226 mm.

|  |                               |
|--|-------------------------------|
| Type of installation                   | Recessed                      |
| Light distribution                     | Direct                        |
| Luminaire shape                        | Circular                      |
| Colour of the luminaires               | White                         |
| Material                               | Aluminium                     |
| Lifetime                               | L80/B20 50 000 hours          |
| Warranty                               | 5 years                       |
| Description of luminaires              | Luminaire recessed            |
| Dimensions                             | $\varnothing$ 185 mm × 100 mm |
| Type of optical system                 | Opal diffuser                 |
| Luminous flux*                         | 1980 lm                       |
| Colour Temperature                     | 3000 K warm white             |
| Luminous efficacy                      | 110 lm/W                      |
| MacAdam Light source                   | 3                             |
| Colour rendering index                 | 80                            |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 17.3                          |
| Luminaire power input*                 | 18 W                          |
| Connection of the luminaires           | ON/OFF + 1h emergency         |
| Electrical voltage                     | 220-240V                      |
| Frequency                              | 50/60Hz                       |

 **CE IP 54**

\* $\pm 10\%$

## Technical drawing



## Curve



## Downloads

Installation instructions



Photos

